



Hand protection

KPG10

THERMAL HOT WORKS

Level D cut-resistant ambidextrous thermal glove, combining thermal resistance and finesse, ideal for use in hot environments



Specific benefits



Easy to use

· Perfect fit so that users do not feel any discomfort in the wrist area with prolonged use



Performance

· The high-performance HEATnocut fiber provides resistance to contact heat (250° for 15 seconds)



Compatibility

· Ambidextrous Glove

Certifications and norms



EN 388
1 X 4 X D



EN 407
4 2 X X X X

Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Maintenance
- Automotive
- Temporary Work

Risk Protection



Heat



Cutting



Hand protection

KPG10

THERMAL HOT WORKS

Level D cut-resistant ambidextrous thermal glove, combining thermal resistance and finesse, ideal for use in hot environments

Standards - Details



EN388:2016+A1:2018

1 [0-4] ABRASION RESISTANCE
X [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
X [0-4] PIERCE RESISTANCE
D [A-F] CUT RESISTANCE ISO 13997



EN 407

THERMAL RISKS (X = NOT TESTED)
4 [0-4] BURNING BEHAVIOUR
2 [0-4] CONTACT HEAT RESISTANCE
X [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
X [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Mechanical glove
Glove family	Knitted uncoated glove
Mechanical Glove Type	Tricot
Fiber	Aramid, Cotton
Gauge	7
Benefits element	Para-aramid stitching
Color	Yellow
Size	9
Type of conditioning	Bulk bag of 12



Safety gloves

KPG10

THERMAL HOT WORKS

Level D cut-resistant ambidextrous thermal glove, combining thermal resistance and finesse, ideal for use in hot environments

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
KPG1009	Yellow	09	KPG10	3295249035433	13295249035430	36	6	7.5 kg	40.0 cm	32.0 cm	31.0 cm



Multiple Sales



Minimum Order Quantity



Box Width



Box Depth



Box Height